



Typ
TS-CZ1540

Technische Daten

Typ:	4-polig
Länge:	58,2mm
Durchmesser:	29mm
Wellendurchmesser:	4mm/3,17mm
Gewicht:	180g

Typ	[Kv]	[Ri]	Max V	Max A	Max Power(W)
TS-CZ1540 *4	5100	4,00	15	130	1200
TS-CZ1540 *5	4130	6,00	18	120	1200
TS-CZ1540 *6	3440	8,00	21	110	1200
TS-CZ1540 *7	2950	10,50	24	100	1200
TS-CZ1540 *8	2580	13,40	28	85	1200
TS-CZ1540 *9	2300	16,50	32	70	1200
TS-CZ1540 *10	2060	20,50	35	65	1200
TS-CZ1540 *11	1880	24,00	38	60	1200
TS-CZ1540 *12	1720	28,00	42	55	1200
TS-CZ1540 *13	1580	32,50	45	50	1200
TS-CZ1540 *14	1480	38,20	50	45	1200
TS-CZ1540 *15	1380	45,00	55	45	1200
TS-CZ1540 *16	1290	48,00	60	40	1200
TS-CZ1540 *17	1200	56,00	60	38	1200
TS-CZ1540 *18	1150	59,00	65	35	1200
TS-CZ1540 *19	1090	70,00	65	32	1200
TS-CZ1540 *20	1030	74,00	70	30	1200
TS-CZ1540 *21	990	78,00	70	28	1200
TS-CZ1540 *22	940	90,00	75	28	1200

Erfolge

2009 Bulgaria ECO-Expert Team 1er Platz

Besonders geeignet für ECO Expert & Hydro